

GLAZING PUTTY (WHITE)

FLEXIBLE - WILL NOT CRACK ON INTERIORS & EXTERIORS

- ◆ LONG-LASTING
- ◆ COMPATIBLE WITH ALL PAINTS & COATINGS
- ◆ DOESN'T STICK TO YOUR HANDS
- ◆ WILL NOT SMEAR GLAZING



PURPOSE

White putty for the glazing of wooden window frames.

SUBSTRATES

Glazing Putty can be applied to any types of woods, including common exotic species, and all primed wood.

The substrate must be previously primed.

Do not use for double glazing fitting.

OVERCOATING

Glazing Putty can be overcoated with paint, varnish or preservative coat once a skin has formed.

Physical and technical FEATURES

- Linseed oil based putty, for interior or exterior use.
- Characterization (NFT 36-005): Family IV class 1.
- Mixing rate: ready to use.
- Coverage: 6m per kg.
- Overcoating: painted/overcoated once a skin has formed (6 to 8 days).
- Color: white.

USE AND STORAGE CONDITIONS

- Application tools: for putty and back putty, apply with a putty knife, for single glazing, glass from 4 to 6mm thick. The minimum thickness of the back putty must be 3mm, the minimum length of the fillet must be 9mm.
- Tool cleaning: after use, clean tools with white spirit.
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from sunlight and frost. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

Tin: 1kg.

RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions. Do not apply at a temperature below 5°C or above 35°C nor at a relative humidity over 80%.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- NFT 36-005: Characterization of paint products.

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Glazing Putty white. Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Safety data sheet available at www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).