

sticker remover



HG sticker remover

LIVING ROOM

• also for tar and heel marks

Removes stickers, sticker glue, sellotape, tar, oil, scuff marks and many other problems from most surfaces.

Directions for use: *HG sticker remover* is used undiluted. Paper stickers: Apply *HG sticker remover* with a brush and repeat a couple of times. Leave to work and then remove the sticker. Finally apply the liquid once more and after a few seconds, remove the remaining glue with a citch. **P.VC.-stickers:** Lift up an edge and let the liquid run behind. Lift up more of the sticker and reapply the liquid s necessary until it is possible to peel it away completely. Finally apply the liquid once more and after a few seconds, remove the remaining glue with a citch.

Attention: Transport and store the bottle upright. Test the resistance of the surface prior to use, for instance with delicate high gloss paint, plastics etc. Not suitable for hard, transparent plastic material (polycarbonate), We advise against washing the used cloth in the washing machine. • Medical personnel can request the data sheet via +31 36 54 94 777 • The consumer's information sheet can be obtained via www.HG.eu

> 30%
< 5%
305
000



Consumer Services?

Call: +44 (0)1279 598360

DANGER H226- Flammable liquid and vapour. H304- May be fatal if swallowed and enters airways, H335- May cause respiratory irritation, H336-May cause drowsiness or dizziness, H411- Toxic to aquatic life with long lasting effects. P101- If medical advice is needed, have product container or label at hand. P102- Keep out of reach of children. P210- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261- Avoid breathing vapours. P271- Use only outdoors or in a well-ventilated area, P301+P310- IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician, P304+P340- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing, P331- Do NOT induce vomiting, P501-Dispose of contents and container in accordance with all local, regional, national and international regulations, Contains; Solvent naphtha (petroleum), light aromatic, EINECS; 265-199-0. Made in The Netherlands by HG International b.v., P.J. Oudwey 1314 CJ Almere, The Netherlands, Tel.: +31 36 54 94 700 UFI: 4Q39-DFEV-900R-TQNP HG Does what it promises. UK importer: HG UKI Ltd, Weston Business Centre, Farsonage Road.

Takeley, Essex, CM22 6PU. Tel.: +44 (0) 1206 822 744