## STUART

### STUART

### Water Conditioner C

WRAS approved and designed to ensure limescale prevention in domestic properties, including water outlets and household appliances.

The Stuart range of Water Conditioners offer a solution to match the typical water flow from the cold water mains to the property and are simply installed in-line with the existing pipework and are completely maintenance free.





#### Features

- Whole house water supply treatment
- Prevents limescale build up maintains appliance efficiency
- Treated water is safe to drink
- Treated water can be stored for up to 3 months
- Compact design easy to install in any orientation
- Environmentally friendly, does not use chemicals or salts
- Maintenance free no ongoing costs
- No electrical power required
- 10 year warranty
- Available in a range of sizes and flow rates

#### **Applications**

- Available in a range of sizes optimised to meet the flow rate requirements of residential properties
- Installed inline with the incoming mains water supply just after the stopcock
- Stuart Water Conditioner products can play an effective role in achieving compliance with Part L of the Building Regulations

# STUART

#### **Product Selection**

Model selection must be based upon actual measured flow and is essential for effective operation.

1) Measure the typical water flow demanded from the cold water mains supply.

2) Select the appropriate Water Conditioner product based on the stated optimum flow range\*.

Model	Water Conditioner 3–22 44617	Water Conditioner 23-45 44618	Water Conditioner 46-75 44619	
Warranty	10 year			
WRAS Approval	1606370			
Conformity Certification	UK CA / CE			
Туре	Catalytic	Catalytic	Catalytic	
Optimum flow*	3-22 l/min	23-45 l/min	46-75 l/min	
Maximum pressure	10 bar			
Housing	Stainless steel			
Connection type	Compression			
Connection Size	15/22 mm**	22 mm	28 mm	
Typical noise	Silent			
Width	265 mm	290 mm	308 mm	
Diameter	27 mm	34 mm	42 mm	
Weight	0.8 Kg	1.0 Kg	1.5 Kg	

\*\*Supplied with 22 mm compression fittings and 15 mm compression reducers



Model	Dim. 'A'	Dim. 'B'	Dim. 'C'
3-22	265 mm	27 mm	22 mm
23-45	290 mm	34 mm	22 mm
46-75	308 mm	42 mm	28 mm



Stuart Turner Limited reserves the right to amend specifications without notice.