# HEALTH AND SAFETY DATA SHEET

PAGE: 1 of 6 DATE: 27.11.2020 ISSUE: 2

### SECTION 1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

- 1.1 Product name: MACXSEAL-WH and MACXSEAL-CL HYBRID Polymer Adhesive/Sealant (Translucent & White)
- **1.2** Use: A moisture curing elastomeric sealant/adhesive for weather proofing and bonding.
- **1.3** Supplier of the safety data sheet:

Registered company address:

Ph: +44 (0) 141 882 3213

McAlpine & Co Ltd.

Kelvin Avenue,

Hillington,

Glasgow,

G52 4LF,

# United Kingdom

e-mail: info@mcalpineplumbing.com

**1.4 Emergency Tel:** +44 (0) **141 882 3213** (office hours only)

# SECTION 2. HAZARDS IDENTIFICATION

- 2.1 Classification of the mixture
- 2.1.1 Regulation EC 1272/2008 Skin sens. 1A: H317
- 2.2 Label elements
- 2.2.1 Regulation EC 1272/2008



Hazard pictograms: Signal word:

### Hazardous components to be indicated on label:

Contains: N-(3-((trimethoxysilyl)propyl)ethylenediamine. Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate & Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate - May cause an allergic skin reaction

Contains 2-Octyl-2H-isothiazol-3-one May cause an allergic reaction

 Hazard statements: H317: May cause an allergic skin reaction EUH 208 Contains 2-Octyl-2H-isothiazol-3-one may cause an allergic reaction
 Precautionary statements: P271: Use in well ventilated areas P280: Wear protective clothing and gloves.
 P222: 242: 242: 242: 4 a bin initiation area on if your feel were This product does not contain any known PBT or vPvB substances

PAGE: 2 of 6 DATE: 27.11.2020 ISSUE: 2

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

22

Ingredient	CAS No.	EINECS	REACH registration No.	Classification According to Reg. (EC) 1278/2008 (CLP)	% W/W
Trimethoxy(vinyl)silane	2768-02-7	220-449-8		Flam Liq 2: H225 Acute Tox. 4: H332	0.1–3%
3-(trimethoxysilyl)propylamine	13822-56-5	237-511-5		Eye dam. 1: H318 Skin Irrit. 2: H315	<1%
N-(3-(trimethoxysilyl)propyl) ethylenediamine	1760-24-3	217-164-6		Acute Tox. 4: H332 Aquatic chronic 2: H411 Skin sens. 1: H317 Eye dam. 1: H317	<1%
Benzenepropanoic acid, 3,5,-bis (1,1-dimethylethyl)-4-hydroxy-, C7-9-branched alkyl esters	125643-61-0	406-040-9		Aquatic chronic 4: H413	<1%
alpha-3-(3-(2H-Benzotriazol-2-yl)- 5-tert-butyl-4-hydroxyphenyl)propionyl- omega-hydroxypoly(oxy-ethylen)	104810-48-2		N/A	Skin sens. 1: H317	<1%
alpha-3-(2H-Benzotriazol-2-yl)-5-tert-butyl- 4-hydroxyphenyl)propionyl)-omega-3-(3- (2H-benzo-triazol-2-yl)-5-tert-butyl-4- hydroxyphenyl)propionyloxypoly(oxyethylen)	104810-47-1				
Bis(1,2,2,6,6-pentamethyl-4-piperidiyl) sebacate	41556-26-7	255-437-1	N/A	Skin sens. 1A: H317 Aquatic chronic 1: H410	<1%
Methyl(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	82919-37-7	280-060-4			
Dioctyltin oxide tetraethylorthosilicate	870-08-6 78-10-4	212-791-1 201-083-8	01-2119971268-27-000 01-2119496195-28-xxx		<1%
2-Octyl-2H-isothiazol-3-one	26530-20-1	247-761-7		Skin Sens.1A H317 Aqu.Chron 3 H412	<0.5%

\*for full text of Hazard statements see section 16.

### SECTION 4. FIRST AID MEASURES 4.1 General: In all cases of

**General:** In all cases of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**Skin Contact:** Wash skin thoroughly with soap and water or a recognised skin cleaner. DO NOT USE SOLVENT OR THINNERS. Seek medical attention if irritation persists.

**Eye Contact:** Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes holding eyelids apart, and seek medical advice.

**Ingestion:** If accidentally swallowed wash mouth with water and give large volumes of water to drink. DO NOT induce vomiting. Seek medical attention.

Inhalation: Remove to fresh air. If symptoms persist, or if in doubt, seek medical attention.

PAGE: 3 of 6 DATE: 27.11.2020 ISSUE: 2

### 4.2 Most important symptoms and effects

**Skin contact:** Prolonged contact may cause irritation and dry skin. **Eye contact:** May affect vision. If irritation persists seek medical advice **Ingestion:** Do not induce vomiting. Wash out mouth with water. Consult a doctor.

### SECTION 5. FIRE FIGHTING MEASURES

- 5.1 Extinguishing Media: Foam, CO<sub>2</sub>, powder, water spray/mist.
- **5.2 Special Hazards:** organic compound so black smoke and carbon monoxide and carbon dioxide Will be released in a fire
- **5.3** Advice for firefighters: Do not allow run off from fire fighting to enter drains or water courses. Wear self-contained breathing apparatus

### SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1: Personal precautions and protective equipment

Avoid skin and eye contact. Wear personnel protective equipment. Ensure adequate ventilation.

**6.2: Environmental precautions** 

Do not allow to enter drains or water courses.

# 6.3: Method for containment and clean up

Contain and collect spillages and place in a suitable container for disposal in accordance with the waste regulations (see section 13). Take action to avoid static electricity discharge.

## SECTION 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited during use. For personal protection see Section 8.

Keep away from sources of ignition. Take precautions to avoid static electricity discharge.

**The Manual Handling Operations Regulations** may apply to the handling of containers/packages of this product. In order to calculate the weight of any pack size, multiply the volume in litres by the specific gravity value given in section 9. This will give the net weight of the product in kilograms.

### 7.2 Precautions for safe storage Keep containers closed when not in use.

**O**bserve label precautions – Store between 5°C and 25°C. in a dry well-ventilated place away from sources of heat. Protect from frost. Keep out of reach of children. Store separately from oxidising agents and strongly acidic materials.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters EXPOSURE LIMITS:

Substance	Oc	cupational Ex	Notations		
	8 hr l	_TEL (1)	15 min S	STEL(2)	
	ppm	mgm⁻³	ppm	mgm <sup>-3</sup>	
dioctyltin oxide		0.1 (WEL)		0.2 (WEL)	
(4) Lana (and a constant la					

- (1) Long-term exposure limit 8 hour time weighted average.
- (2) Short-term exposure limit 15 mins time weighted average.
- (3) WEL workplace exposure limit

### **8.2 Exposure Controls**

Engineering Measures: Provide adequate ventilation during application and drying.

### **Respiratory equipment**

If ventilation is insufficient suitable respiratory protective equipment must be worn.

Skin & Hand protection Wear suitable protective clothing and plastic or rubber gloves.

### Eye protection

Eye protection designed to protect against liquid splashes should be worn. Equipment should conform to EN166 **Hygiene measures** 

When using do not eat drink or smoke. Wash hands before eating, drinking, smoking or using the toilet.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

viscous paste	
slight	
N/Ā	
Translucent - 1.0-1.05	⊉ 20 °C
Colours - 1.45 - 1.50 @	20 <sup>0</sup> C
not soluble in water.	
Trans:- 22g/ltr	Colours: - 35g/ltr
	slight N/A Translucent - 1.0-1.05 @ Colours - 1.45 - 1.50 @ not soluble in water.

### SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under normal temperature and storage conditions

10.3 Possibility of hazardous reactions

None known

10.4 Conditions to avoid

Strong acids, bases and oxidising materials

10.5 Incompatible materials

See section 10.4

10.6 Hazardous decomposition products

See section 5

### SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological effects not established.

Ingestion:	May cause discomfort if swallowed. May cause stomach pain and nausea
Skin contact:	May cause an allergic skin reaction
Eye contact:	Risk of damage to eyes.
Inhalation:	not significant
Sensitisation:	Not sensitising
STOT:	Not classified

### SECTION 12. ECOLOGICAL INFORMATION

# 12.1 Ecotoxicity No data available 12.2 Persistance and degradeability Biodegradation only slightly biodegradeable. 12.3 Bio accumulative potential No data available 12.4 Mobility in soil No data available

PAGE: 5 of 6 DATE: 27.11.2020 ISSUE: 2

### **DISPOSAL CONSIDERATIONS** SECTION 13.

13.1 Waste treatment methods

Dispose of this material as hazardous or special waste in accordance with local or national requirements.

### **SECTION 14 TRANSPORT INFORMATION**

This product is not covered by International regulation on the transport of dangerous goods.

- 14.1 UN number: not applicable
- 14.2 Proper shipping name: not applicable
- not applicable 14.3 Transport hazard class:
- 14.4 Packing group:
- Environmental hazards: Not classed as Marine pollutant 14.5
- Special precautions for users: 14.6 no. see section 7
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC code: 14.7 Not applicable

not applicable

### **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1 Regulation (EC) 1272/2008 (CLP) Control of Substances Hazardous to Health Regulations 1999

Environment Act 1995 Management of Health and Safety at Work Regulations 1999 Personal Protective Equipment at Work Regulations 1992 Special Waste Regulations 1996 as amended

### HEALTH AND SAFETY EXECUTIVE GUIDANCE NOTES

HS(G)37	An Introduction to Local Exhaust Ventilation
EH40	Occupational Exposure Limits
EH44	Dust: General Principles of Protection
HS(G)53	The Selection, Use and Maintenance of Respiratory Protective Equipment
HS(G)71	Storage of Packaged Dangerous Substances
HS(G)193	COSHH Essentials: easy steps to control chemicals
L23	Manual Handling Guidance on Regulations

### **BRITISH STANDARDS PUBLICATIONS**

- **General Requirements for Gloves** EN420:
- Personal Eye Protection: Specifications EN166: Eve Protection for Industrial and Non-Industrial Users BS2092: BS4275: Recommendations for the Selection, Use and Maintenance of Respiratory **Protective Equipment**

### 15.2 **Chemical safety assessment**

A chemical safety assessment has not been carried out

### SECTION 16. **OTHER INFORMATION** Symbols and text used in sections 2 and 3

Hazard statements:

H225	Highly Flammable liquid and vapour
H226	Flammable liquid and vapour
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness and dizziness

H371 May cause damage to the immune systemH410 Very toxic to aquatic life with long lasting effects

PAGE: 6 of 6 DATE: 27.11.2020 ISSUE: 2

H411 Toxic to aquatic life with long lasting effectsH413 May cause long lasting harmful effects to aquatic life

The information contained in the Health and Safety Data Sheet is provided in accordance with the requirements of the CLP Regulations. The product should not be used for purposes other than those identified without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information contained in the safety data sheet is based on present knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular application.