





# PRODUCT DATA SHEET

# **EVERBUILD® JETCEM WATERPROOF**

Rapid setting repair cement.

#### PRODUCT DESCRIPTION

EVERBUILD® JETCEM WATERPROOF is a cement based mix, formulated specifically for water resistance and is designed to set hard in about 30 minutes.

# **USES**

- Repairs to cracks and holes in structures subject to permanent water immersion.
- Patching repairs to tanking & water retaining structures
- Repairs to ponds and pools.
- Ideal for repairs to steps in basements, and areas susceptible to damp.
- Seal and joint drains and pipes.
- Filling around pipes, through gaps.
- Bedding sanitary ware (pedestal, toilets etc).

# **CHARACTERISTICS / ADVANTAGES**

- Rapid setting (30 minutes, depending on ambient temperature and conditions).
- Easy mixing, just add water.
- Waterproof once cured.
- Fast, strong and easy to use.
- Use on concrete, stone and brick.

# **APPROVALS / STANDARDS**

Conforms to BS EN 1504-3 Class R3.

#### PRODUCT INFORMATION

Chemical Base	Cement based.
Packaging	3 kg Bag.
Shelf Life	12 months in unopened bags.
Storage Conditions	Store in cool dry conditions between +5 °C and +25 °C. Storage outside these parameters will significantly reduce shelf life.
Appearance / Colour	Grey powder.
Density	1.5 g/cm <sup>3</sup>

# **VALUE BASE**

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

# **LIMITATIONS**

- EVERBUILD® JETCEM WATERPROOF should not be used for load bearing applications. Use Everbuild® Anchorset.
- Do not use on holes deeper than 25 mm. Large voids may be filled with Everbuild\* Fix and Fill Expanding foam then finished with EVERBUILD® JETCEM WA-

Product Data Sheet EVERBUILD® JETCEM WATERPROOF October 2022, Version 01.03 020701010010000257 TERPROOF once cured.

- Repairs to ponds and pools must be sealed with a suitable paint before re-filling.
- Not approved for contact with drinking water.
- Do not use where chemical resistance is required. Use Everbuild® EPOXYSET 105 Standard Cure.
- It is always the user's responsibility to determine suitability of use. If in doubt contact Technical Services department.

### **ECOLOGY, HEALTH AND SAFETY**

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

#### **APPLICATION INSTRUCTIONS**

#### SUBSTRATE QUALITY / PRE-TREATMENT

Make sure repair area is clean and free from grease, dust and dirt, then thoroughly wet the surface.

#### **MIXING**

Using clean, dry tools, mix 3 parts EVERBUILD® JETCEM WATERPROOF with 1 part by volume clean, cold water to a smooth paste.

IMPORTANT - Do not mix more cement than can be used in 5-10 minutes.

#### **APPLICATION**

Apply the mixture immediately with a trowel or knife, working well into area to be repaired.

Level with surrounding area before mixture starts to set, usually within 10 minutes. Repairs to ponds and pools must be sealed with a suitable paint before re-

#### **CLEANING OF TOOLS**

Clean all tools immediately with water. Store bag sealed and closed, in a cool, dry place away from children and pets.

#### LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

#### **EVERBUILD BUILDING PRODUCTS LTD**

Site 41, Knowsthorpe Way Cross Green Industrial Estate Leeds, LS9 0SW Tel: 0113 240 3456 Web: www.everbuild.co.uk Twitter: @everbuild

WATERPROOF October 2022. Version 01.03

#### SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited

#### **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILDJETCEMWATERPROOF-en-GBEVER-(10-2022)-1-3.pdf





