

POCKET DOOR HENDERSON

60kg

Wood

Interior

Sliding door solution that works with cavity walls for doors up to 60kg

Overview

Pocket Door is a unique sliding door solution whereby the sliding door disappears into the cavity wall. The system offers amazing benefits for environments where space is limited such as bathrooms, en suites, kitchens, utility rooms, walk in wardrobes and disability access areas. Each Pocket Door kit comes with a pre-assembled aluminium track and header mechanism. For bi-parting doors, two kits can be used.

The system is available with an included dual soft close which catches the door in its final moments of travel and brings it gently into position - preventing slamming.

Features and Benefits

- Six kits available for various opening widths (can be modified to suit bespoke door sizes)
- Each kit comes complete with the stud supports to create a cavity
- Available as standard or dual soft close kits
- Bi-parting and simultaneous option available (order code SIM100)
- Supplied with flush pulls (x2)
- Compatible locksets available in gold or satin (see accessories)
- Overall wall thickness with 12.5mm boards is 120mm



Product and Door Specification




Kit Order Code		Door Thickness Range	Max. Door Width	Max. Door Height
Standard Pocket Door (Doors weighing upto 60kg)	Pocket Door with Dual Soft Close (Doors weighing 10-60kg)			
PDK3	PDKSOFT3	28-44mm	762mm	1981mm
PDK4	PDKSOFT4	28-44mm	838mm	1981mm
PDK5	PDKSOFT5	28-44mm	762mm	2040mm
PDK6	PDKSOFT6	28-44mm	826mm	2040mm
PDK7	PDKSOFT7	28-44mm	726mm	2040mm
PDK10	PDKSOFT10	28-44mm	930mm	2315mm

Kit Contents			Accessories			
	Standard	Soft Close				
Aluminium Track (x1)	280M	280HP	Simultaneous Action Kit	For two bi parting doors (2 pocket door kits required)	SIM100	
Hangers (x2)	284	284HP				
Galvanised Steel Wrapped Softwood Studs (x4)	-	-	Lockset	For 35-52mm thick doors (satin)	390/S	
Galvanised Steel Stud Spacing Brackets (x2)	-	-		For 35-52mm thick doors (chrome)	390/C	
Galvanised Steel Stud Support Brackets (x2)	-	-				
Softwood Header Assembly (with pre-fitted track) (x1)	-	-				
Clip Stop with Adjustable Retention (x2)	601H	(N/A)	Door Edge Pull	Finger pulley in satin	EDGE/S	
Soft Close Kit (x1)	(N/A)	SOFTHP120		Finger pulley in chrome	EDGE/C	
Rubber Buffer (x1)	287	(N/A)				
Flush Pulls (x2)	385SA	385SA				
Guide (x1)	PD/WRAP	PD/WRAP				

Watch the Installation Video

Visit www.pchenderson.com/pocket-door-installation or scan the QR code using your phone





Opening Size Guide

Kit	Standard Door Size	Rough Opening Width	Rough Opening Height
PDK3	762mm (w) x up to 1981mm (h)	1554mm	2071mm
PDK4	838mm (w) x up to 1981mm (h)	1706mm	2071mm
PDK5	762mm (w) x up to 2040mm (h)	1554mm	2130mm
PDK6	826mm (w) x up to 2040mm (h)	1682mm	2130mm
PDK7	726mm (w) x up to 2040mm (h)	1482mm	2130mm
PDK10	930mm (w) x up to 2315mm (h)	1890mm	2405mm

Finished Wall Thickness Calculation

120mm Finished Wall Thickness

95mm cavity + 12.5mm plasterboard either side = 120mm finished wall thickness

For further information, please contact us on:

UK Sales

T: **+44 (0) 191 377 7345**

E: **sales@pchenderson.com**

W: **www.pchenderson.com**

Export Sales

T: **+44 (0) 191 377 7346**

E: **international@pchenderson.com**

W: **export.pchenderson.com**