EASY ALGAE REMOVER

Page: 1

Compilation date: 13/03/2014

Revision date: 11/03/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: EASY ALGAE REMOVER

Product code: 2610

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC8: Biocidal products (e.g. Disinfectants, pest control). HSE biocide licence number 9648

1.3. Details of the supplier of the safety data sheet

Company name: AZPECTS LTD UNIT 13 RIVERSIDE INDUSTRIAL PARK RAPIER STREET IPSWICH IP2 8JX Tel: 01473 412658

Email: info@azpects.co.uk

1.4. Emergency telephone number

Emergency tel: 01473 760777 (office hours only)

Section 2: Hazards identification

| 2.1. Classification of the s | 2.1. Classification of the substance or mixture | | | | | |
|---|---|--|--|--|--|--|
| Classification under CLP: Skin Corr. 1B: H314; Met. Corr. 1: H290; Acute Tox. 4: H302; Aquatic Acute 1: | | | | | | |
| H400 | | | | | | |
| Classification under CHIP: C: R34 | | | | | | |
| Most important adverse effects: | Causes severe skin burns and eye damage. May be corrosive to metals. Harmful if | | | | | |
| swallowed. Very toxic to aquatic life. | | | | | | |

2.2. Label elements

| Label elements under CLP: | |
|---------------------------|--|
| Hazard statements: | H314: Causes severe skin burns and eye damage. |
| | H290: May be corrosive to metals. |
| | H302: Harmful if swallowed. |
| | H400: Very toxic to aquatic life. |
| Signal words: | Danger |
| Hazard pictograms: | GHS05: Corrosion |
| | GHS09: Environmental |

EASY ALGAE REMOVER

Page: 2



Precautionary statements:P102: Keep out of reach of children.P264: Wash hands thoroughly after handling.P280: Wear protective gloves/protective clothing/eye protection/face protection.P271: Use only outdoors or in a well-ventilated area.P260: Do not breathe vapour.P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.Remove contact lenses, if present and easy to do. Continue rinsing.P501: Dispose of to In accordance with national/local regulations.P405: Store locked up.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIDECYLDIMETHYLAMMONIUM CHLORIDE

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|-----------|-----------|---------------------|--|---------|
| 230-525-2 | 7173-51-5 | - | Acute Tox. 4: H302; Skin Corr. 1B: H314 | 5-10% |

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C8-18-ALKYLDIMETHYL, CHLORIDES

| 264-151-6 | 63449-41-2 | - | Acute Tox. 4: H312; Acute Tox. 4: | 4.9-5% |
|-----------|------------|---|------------------------------------|--------|
| | | | H302; Skin Corr. 1B: H314; Aquatic | |
| | | | Acute 1: H400 | |

PROPAN-2-OL

| 2 | 200-661-7 | 67-63-0 | - | Flam. Liq. 2: H225; Eye Irrit. 2: | 0.9- |
|---|-----------|---------|---|-----------------------------------|------|
| | | | | H319; STOT SE 3: H336 | 2.4% |

BIPHENYL-2-OL

| 201-993-5 | 90-43-7 | - | Eye Irrit. 2: H319; STOT SE 3: | 0.9- |
|-----------|---------|---|------------------------------------|------|
| | | | H335; Skin Irrit. 2: H315; Aquatic | 2.4% |
| | | | Acute 1: H400 | |

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

EASY ALGAE REMOVER

- **Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
 - Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
 - Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

- **Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
- Eye contact: Corneal burns may occur. May cause permanent damage.
 - **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
 - **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without

EASY ALGAE REMOVER

suitable protective clothing - see section 8 of SDS. Turn leaking containers leakside up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PROPAN-2-OL

Workplace exposure limits:

| State 8 hour TWA | | 15 min. STEL | 8 hour TWA | 15 min. STEL | |
|------------------|-----------|--------------|------------|--------------|--|
| UK | 999 mg/m3 | 1250 mg/m3 | - | - | |

Respirable dust

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

EASY ALGAE REMOVER

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| State: | Liquid |
|------------------------|--------------------------|
| Colour: | Off-white |
| Odour: | Barely perceptible odour |
| Evaporation rate: | Slow |
| Solubility in water: | Highly soluble |
| Viscosity: | Non-viscous |
| Boiling point/range°C: | 100 |
| pH: | Approx. 7 |

Flash point°C: >93 VOC g/l: 15

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Page: 5

EASY ALGAE REMOVER

Hazardous ingredients:

DIDECYLDIMETHYLAMMONIUM CHLORIDE

| IPR | RAT | LD50 | 45 | mg/kg |
|-----|-----|------|-----|-------|
| ORL | MUS | LD50 | 268 | mg/kg |

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C8-18-ALKYLDIMETHYL, CHLORIDES

| IVN | MUS | LD50 | 16 | mg/kg |
|-----|-----|------|-----|-------|
| ORL | MUS | LD50 | 150 | mg/kg |

PROPAN-2-OL

| IVN | RAT | LD50 | 1088 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 3600 | mg/kg |
| ORL | RAT | LD50 | 5045 | mg/kg |
| SCU | MUS | LDLO | 6 | gm/kg |

BIPHENYL-2-OL

| ORL | MUS | LD50 | 1050 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 2700 | mg/kg |

Relevant effects for mixture:

| Effect | Route | Basis |
|-------------|-------------|-----------------------|
| Corrosivity | OPT INH DRM | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

EASY ALGAE REMOVER

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: WEAR PROTECTIVE CLOTHING AT ALL STAGES OF HANDLING THIS PRODUCT

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

EASY ALGAE REMOVER

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment Section 16: Other information Other information Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010. * indicates text in the SDS which has changed since the last revision. Phrases used in s.2 and 3: H225: Highly flammable liquid and vapour. H290: May be corrosive to metals. H302: Harmful if swallowed. H312: Harmful in contact with skin. H314: Causes severe skin burns and eye damage. H315: Causes skin irritation. H319: Causes serious eye irritation. H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness. H400: Very toxic to aquatic life. R34: Causes burns. Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.