# FLEXIGLASS CATALYST

Page: 1

Compilation date: 27/01/2018

Revision No: 1

#### Section 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

# Product name: FLEXIGLASS CATALYST

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of substance / mixture: Hardener for polyester resin

# 1.3. Details of the supplier of the safety data sheet

### Company name: Cromar Building Products Ltd

Units 3, 4 & 5 Northside Industrial Park
Selby Road
Whitley Bridge
North Yorkshire
DN14 0GH
United Kingdom
Tel: 01977663133
Fax: 01977662186

Email: sales@cromar.uk.com

# 1.4. Emergency telephone number

# Section 2: Hazards identification

2.1. Classification of the substance or mixture		
Classification under CLP:	Org. Perox. EF: H242; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Acute 1: H400;	
	Aquatic Chronic 2: H411; Aquatic Chronic 1: H410	
Most important adverse effects:	Heating may cause a fire. May cause an allergic skin reaction. Causes serious eye	
	irritation. Very toxic to aquatic life with long lasting effects.	
2.2. Label elements		

# Label elements:

Hazard statements:	H242: Heating may cause a fire.	
	H317: May cause an allergic skin reaction.	
	H319: Causes serious eye irritation.	
	H410: Very toxic to aquatic life with long lasting effects.	
Hazard pictograms:	GHS07: Exclamation mark	
	GHS02: Flame	

GHS09: Environmental



FLEXIGLASS CATALYST

Signal words:	Warning
Precautionary statements:	P220: away from clothing/strong acids, bases, heavy metal salts and other reducing
	substances /combustible materials.
	P233: Keep container tightly closed.
	P235: Keep cool.
	P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
	P262: Do not get in eyes, on skin, or on clothing.
	P273: Avoid release to the environment.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P333+313: If skin irritation or rash occurs: Get medical.
	P337+313: If eye irritation persists: Get medical.
	P362+364: Take off contaminated clothing and wash it before reuse.
	P501: Dispose of to approved waste disposal plant.
2.2 Other hererde	

2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

# 3.2. Mixtures

### Hazardous ingredients:

# DIBENZOYL PEROXIDE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-327-6	94-36-0	-	Skin Sens. 1: H317; Org. Perox. B: H241; Eye Irrit. 2: H319	30-50%
ALCOHOLS, C	12-15, ETHOXYL	ATED, PROPOXYLATED		
-	68551-13-3	-	Eye Dam. 1: H318; Aquatic Acute 1:	<1%

# Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

H400; Aquatic Chronic 1: H410

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**Page:** 2

# FLEXIGLASS CATALYST

4.2. Most important symptoms	and effects, both acute and delayed
Skin contact:	There may be irritation and redness at the site of contact.
Eye contact:	There may be irritation and redness. The eyes may water profusely.
Ingestion:	There may be soreness and redness of the mouth and throat.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may
	cause coughing or wheezing.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.
4.3. Indication of any immedia	te medical attention and special treatment needed
Immediate / special treatment:	Eye bathing equipment should be available on the premises.
Section 5: Fire-fighting measu	ires
E.1. Extinguishing modio	
5.1. Extinguishing media	
Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used. Use water spray
	to cool containers.
5.2. Special hazards arising from	om the substance or mixture
Exposure hazards:	In combustion emits toxic fumes.
5.3. Advice for fire-fighters	
Advice for fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact
0	with skin and eyes.
Section 6: Accidental release	
6.1. Personal precautions, pro	tective equipment and emergency procedures
Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from
	downwind. If outside keep bystanders upwind and away from danger point. Mark out the
	contaminated area with signs and prevent access to unauthorised personnel. Turn
	leaking containers leak-side up to prevent the escape of liquid.
6.2. Environmental precaution	s

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

### FLEXIGLASS CATALYST

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

# 8.1. Control parameters

# Hazardous ingredients:

#### **DIBENZOYL PEROXIDE**

#### Workplace exposure limits:

#### **Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	-	-	-

### **DNEL/PNEC** Values

DNEL / PNEC No data available.

#### 8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Protective gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Protective clothing.

#### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	White		
Odour:	Characteristic odour		
Evaporation rate:	Not applicable.		
Oxidising:	Not applicable.		
Solubility in water:	Insoluble		
Viscosity:	Viscous		
Kinematic viscosity:	1 mPa.s		
Boiling point/range°C:	No data available.	Melting point/range°C:	No data available.
Flammability limits %: lower:	Not applicable.	upper:	Not applicable.
Flash point°C:	Not applicable.		

#### FLEXIGLASS CATALYST

#### Page: 5

Part.coeff. n-octanol/water: Not applicable.

Vapour pressure: Not applicable.

pH: Not applicable.

Autoflammability°C: Not applicable. Relative density: 1.2

VOC g/l: Not applicable.

# 9.2. Other information

Other information: Self-Accelerating decomposition temperature (SADT) - 50 deg.C

#### Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

# 10.4. Conditions to avoid

#### Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases. Heavy metals and heavy metal salts. Reducing agents.

Oxidising agents.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

### 11.1. Information on toxicological effects

# Hazardous ingredients:

### DIBENZOYL PEROXIDE

ORL	MUS	LD50	5700	mg/kg
ORL	RAT	LD50	7710	mg/kg

#### **Relevant hazards for product:**

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### FLEXIGLASS CATALYST

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# Section 12: Ecological information

12.1. Toxicity

#### **Ecotoxicity values:**

Species	Test	Value	Units
Daphnia magna	48H EC50	0.11	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H ErC50	0.0602	mg/l

#### 12.2. Persistence and degradability

#### Persistence and degradability: Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

# 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

# Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
Disposal of packaging:	Dispose of container as un-used product
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.

# Section 14: Transport information

#### 14.1. UN number

UN number: UN3107

#### FLEXIGLASS CATALYST

# 14.2. UN proper shipping name

#### Shipping name: ORGANIC PEROXIDE, TYPE E, LIQUID (DIBENZOYL PEROXIDE)

# 14.3. Transport hazard class(es)

#### Transport class: 5.2

# 14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

# Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H241: Heating may cause a fire or explosion.
	H242: Heating may cause a fire.
	H317: May cause an allergic skin reaction.
	H318: Causes serious eye damage.
	H319: Causes serious eye irritation.
	H400: Very toxic to aquatic life.
	H410: Very toxic to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.