

STAIN BLOCK DAMP SEAL

Thompson's Stain Block Damp Seal permanently covers damp, water and other household stains. It can be applied directly onto damp walls and ceilings.



COMPOSITION

Thompson's Stain Block Damp Seal is a low odour, solvent based, highly pigmented, acrylic system.

PROPERTIES

Viscosity – Viscous structured liquid.

VOC Content – Very High (>50% w/v).

Odour – Lower odour than most conventional solvent systems.

AREAS OF APPLICATION

All interior walls and ceilings.

PREPARATION

It's important to make sure the cause of damp has been rectified before painting, otherwise it'll just come back. Open doors & windows to make sure the room is well ventilated. Remove any wallpaper and flaking paint with a damp cloth. Fill any cracks or holes, if needed. You can apply this onto damp surfaces, just make sure they're not dripping wet.

APPLICATION

Give the tin a really good stir. Apply with a brush or roller. Apply the paint over the affected area, plus about 30cm around it.

COVERAGE

Thompson's Stain Block Damp Seal will cover 5m² per litre. Coverage will depend on the texture & type of surface you're coating.

DRYING TIME

Thompson's Stain Block Damp Seal will be touch dry in 2 hours. You can decorate over it after 4 hours. Dry times will vary depending on the texture & type of surface you're coating.

CLEANING OF TOOLS

All equipment should be cleaned immediately after use with white spirit or brush cleaner.

Remove as much product as possible from equipment before cleaning.

MAINTENANCE

Further applications of Thompson's Stain Block Damp Seal should not be necessary. If staining reoccurs, the source of the damp has not been correctly rectified.

IMPORTANT NOTES

- Always read the instructions carefully before use.
- Don't apply if air or surface temperature is below 10°C.
- Do not use on exterior surfaces, below ground level or where efflorescence is present.
- Make sure all causes of damp, including structural, plumbing faults and rising damp, are repaired before treatment.

STORAGE

Store in a cool, well ventilated place away from heat and sources of ignition. Store upright and carefully reseal partly used containers.

The shelf life of the product in airtight containers is at least 3 years.

Always store in ambient conditions away from temperature extremes.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flash point 40°C.

Flammable product.

Keep away from sources of ignition. No smoking.

SUPPLY

Obtainable from DIY outlets, paint suppliers and builders' merchants.

SIZES

250ml, 750ml & 2.5L.

DISPOSAL

Don't empty any left over product into drains or watercourses.

Your local authority may have special ways to get rid of waste coatings.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Thompson's products are available on request from our Technical Services Department.