Hep2 Demounting Tool Guide

One of the unique advantages of Hep₂O is that it can be easily demounted and adjusted by the installer, but once fitted the joint is safe and secure and cannot be tampered with or accidentally demounted. To deal with all situations we have three demounting options;

HepKey™

The standard HepKey[™] is the easiest and quickest way to demount a fitting. HepKey[™] simply clips around the pipe and depresses the inner sleeve of the fitting. This opens the 316 stainless steel grab ring and releases the pipe.

HepKey[™] Plus

HepKey[™] Plus enables the installer to remove the fitting with one hand for example when working in a confined space such as under floor boards. It works by clipping onto the fitting and holding the grab ring open allowing the pipe to be pulled out whilst leaving one hand free. HepKey and HepKey plus are available in 10mm, 15mm, 22mm and 28mm versions and are colour coded to match the packaging so are always easy to locate.

HepTool

This specialist metal demounting tool can help in restricted spaces, for example where a fitting is hard up against a wall or another fitting. The slimline spanner can get into awkward areas and allows greater flexibility. The HepTool can also be used to demount some of the reducer fittings in the range (see website for details). HepTools are available in 2 formats – 15mm/22mm and 10mm/28mm.

Comparison

	НерКеу™	HepKey [™] Plus	HepTool
Easy and quick to use in most circumstances	1	1	
One handed demounting – e.g. restricted access		1	
Demounting fittings sited in tight spaces			1
Product code	10mm - HX78/10 15mm - HX78/15 22mm - HX78/22 28mm - HX78/28	10mm - HX79/10 15mm - HX79/15 22mm - HX79/22 28mm - HX79/28	10/28mm - HX77/10 15/22mm - HX77/15

HepKey[™] and HepKey Plus[™] can be purchased from your Hep₂O stockist and HepTools can be requested by emailing info@hep2o.co.uk





НерКеу™



HepKey[™] Plus



HepTool



Professional Push-fit Plumbing.