

FROM ACRYPOL PRODUCTS LTD...

# ACRYPOL +



ACRYPOL+ roof coating was specifically developed to provide a solution for carrying out the day to day maintenance requirements of those involved in roof waterproofing protection. As with most water penetration problems associated with leaking roofs, the need to carry out remedial repairs is very rarely possible during long spells of inclement weather. This is mainly due to the fact that in order to carry out an effective long term repair to leaking roofs, it is generally necessary to ensure that the surfaces to be treated are completely dry.



ACRYPOL+ can be applied during damp weather conditions and at the same time provide a long term solution to the problem. The all-weather application properties, combined with the simplicity of application, makes this product a particularly attractive proposition to those employing their own labour for general property maintenance. The versatility of ACRYPOL+ is acknowledged widely by Municipal Authorities and Maintenance Contractors throughout the United Kingdom.



IN SOLAR WHITE

## ALL WEATHER APPLICATION WATERPROOF ROOF COATING

Available in packs 8 x 2.5kg, 4 x 5kgs or drums of 20kgs

T 01925 213655    E [info@acrypolproducts.co.uk](mailto:info@acrypolproducts.co.uk)    W [www.acrypolproducts.co.uk](http://www.acrypolproducts.co.uk)  
A 4 Asher Court, Lyncastle Way, Barleycastle Lane, Appleton, Warrington WA4 4ST







**CAN BE APPLIED ON ALMOST ANY TYPE OF SURFACE**

**FLAT ROOFS • ASPHALT • BITUMINOUS SURFACES • BRICKWORK**

**GUTTERS • LEADWORK • METALS • PVC • ASBESTOS • GLASS**

**ROOFING FELT • ROOF LIGHTS • CONCRETE • FIBRE GLASS**

**ACRYPOL+** is an acrylic resin dispersed in a solvent to form a semi-liquid paste. The coating film dries into a tough durable elastic overlay that prevents the passage of water, yet is chemically structured to allow trapped moisture to evaporate, thus avoiding the formation of blisters. A specific feature is incorporated with added fibres, fibres that act like a built-in scrim. These fibres interlace when the coating is applied – filling and bridging gaps and cracks (up to 10mm wide). The fibres increase the tensile strength of the dry film making it more durable – **A BIG PLUS!**

**ACRYPOL+** is available in two standard colours, Solar White for maximum solar protection of the roof surface, and Medium Grey generally used for day to day patching repairs where it is preferable to blend the coating into surrounding building material colours.

Special attention should be given to the preparation if Aluminium, Zinc, Fibre Glass, Galvanised or Corroded Metal. Refer to Acrypol Products Limited for instructions.

**WATERPROOF  
SEAMLESS  
ROOF  
MEMBRANE**

### TECHNICAL DATA

#### COVERAGE

1-2kg/m<sup>2</sup> average  
(See application guide, available on request)

#### DRYING TIME

2-3 days depending on ambient temperature and ventilation

#### FLASH POINT

21oc - 55oc

#### SHELF LIFE

Several years with lid secure

#### COLOUR

Solar White or Medium Grey  
(other colours available on special order)

#### CLEANING

Use Acrypol Cleaner to clean equipment

#### STORAGE

Store in even moderate temperature

