

TECHNICAL DATA

Geocel® Decorators Caulk

For Internal and External Use

Paintable within One Hour



Geocel® Contractors Decorators Caulk is a one part, easy to apply flexible acrylic filler which is ideal for sealing gaps and cracks prior to decorating.

It has been specifically developed for the painting and decorating contractor where large volume usage is expected.

Geocel® Contractors Decorators Caulk is ideal for:

- Internal and external pointing around door and window frames
- Sealing around skirting boards and architraves
- Sealing joints between plaster board panels
- Sealing gaps and cracks in plaster
- Conforms to BS EN 15651-1

SPECIFICATIONS

Manufactured under ISO 9001

TECHNICAL DATA

Storage Life	24 months stored in original containers between 4°C and 25°C
Colours	White, Brown, Magnolia
Base	Water based acrylic
Skin Time	30 – 45 minutes
Service Temperature	-10°C to +80°C
Application Temperature	+5°C to +40°C
Slump	Nil

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Geocel® Sales Representative prior to writing specifications on this product.

SURFACE PREPARATION

Ensure that all surfaces are clean, dry, sound and grease free. Provide a key to gloss painted surfaces. Cover nail or screw heads with oil based paint and allow to dry.

APPLICATION

Ensure gaps or cracks to be filled are free from dust, dirt and grease and surfaces are dry. Deep gaps should be half filled with tissue paper before application.

Remove nozzle and cut tip to required width. Place cartridge in cartridge gun and apply material into gap or crack to be filled.

Ensure Geocel® Contractors Decorators Caulk makes full contact with sides and back of the joint. Smooth surface lightly with a damp cloth after application.

Uncured sealant can be cleaned up immediately using a damp cloth or sponge.

LIMITATIONS

- Do not apply to wet surfaces.
- Over wetting may washout the filler or slow the cure rate.
- Geocel® Contractors Decorators Caulk can be painted in 1 hour, dependent on climate conditions.
- Store in a cool dry place, away from frost.

PACKAGING

Geocel® Contractors Decorators Caulk is supplied in 380ml cartridges packed in boxes of 20.

HEALTH AND SAFETY

Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Geocel® Technical Service.

Important Note: The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damage.