

## SARISHOWER® Flat



**Low activation level:** 30 mm.

Ultra flat waste compatible with most trays.




Pump and waste for low level shower tray.

Low height shower tray: 80 mm.

**Small pump** that can be easily hidden from view.

## SEMI-TRANSPARENT VIEW



				PI	ЈМР С	URVE				
Dis	scharge	e heigh	t (m)							
5			_							
4				· ·		-				
3	Maxin	num re	comme	nded l	neight :	3 m				
2										
1										
0	) !	5 1	0 1	5 2	0 2	5 7	iO 3	5 4	0 4	5 50
	,	, ,		, ,	· 2				v rate (	

TECHNICAL FEATURES						
Evacuation height	30 mm					
Shower tray height	80 mm					
Maximum flow rate	70 L/min					
Number of inlets	2					
Ø inlet	32 mm (shower) 40 mm (basin)					
Ø discharge pipework	32 mm					
Voltage	220-240 V/50Hz					
Motor power	250W					
Maximum current	1.3A					
Electrical class	Single phase					
Maximum temperature	35 °C					
IP rating	IP44					
Weight	3.7kg					

PACKAGING						
Pump, tray and waste						
Non-return valve						
Connectors						
INSTALLATION DIAGRAM						
30 mm						

## **APPLICATIONS**





**PUMPING DISTANCE** 

3 m

WARRANTY



Product Code: 1043/3

**Barcode:** EAN 3308815061016

