MAINSBOOST

MBS

Designed for direct on mains systems (unvented cylinders and combination boilers) where the mains pressure is greater than 2.5 bar but water flow is inadequate.

MAINSBOOST MBS vessels are installed directly onto the incoming water supply and under mains pressure fills with water. The MAINSBOOST vessel system now has a volume of pressurised water ready for distribution throughout the property.

For properties with greater demand, MAINSBOOST add-on units can be used to expand storage capacity.



5 YEAR WARRANTY

UK CA CE

Features

- 5 year warranty
- Up to 80 litres/minute per vessel
- 100 – 2000 litre pressure vessel options
- Minimal maintenance
- Silent operation
- Consumes no electricity
- Robust construction
- Long life butyl diaphragm
- Integral strainer
- Comprehensive MONOBLOC installation kit included

Applications

- Boosting the cold water mains supply to domestic properties

Options


- Add-on vessel units can be used to further expand storage capacity
- Vertical and horizontal options available
- CHARGER pump option for applications where the incoming mains water pressure is less that 2.5 bar (static pressure)
- Thermal insulating jackets (optional)

MAINSBOOST MBS									
GENERAL	Warranty					5 years			
	Conformity certification					UKCA | CE			
PERFORMANCE	Maximum working pressure*					1000 kPa (10 bar)			
	Min / Max operating temperature					Min 4 °C / Max 35 °C			
	Max rated temperature					90 °C			
CONSTRUCTION	Pressure vessel					Epoxy coated mild steel			
	Membrane					Butyl rubber			
	Model	**Vessel capacity (litres)****	**Dimensions (mm)**			**Weight empty (Kg)**	**Weight filled (Kg)**	**Maximum weight (Kg)*****	**ULK Kit (mm)**
			H	**W**	**D**				
MBS vessels (vertical)	MB 100SV	55.0	890	410	410	19.7	74.7	119.7	22/28
	MB 130SV	71.5	1100	410	410	23.7	95.2	153.7	22/28
	MB 200SV	110.0	1030	535	535	35.7	145.7	235.7	22/28
	MB 250SV	137.5	1210	535	535	40.7	178.2	290.7	22/28
	MB 300SV	165.0	1505	535	535	49.2	214.2	349.2	22/28
	MB 450SV	247.5	1545	660	660	74.2	321.7	524.2	22/28
	MB 750SV	412.5	1834	756	756	115.9	528.4	865.9	35
	MB 1000SV	550.0	2376	806	806	153.5	703.5	1153.5	35
	MB 1500SV	825.0	2435	960	960	246.4	1071.4	1746.4	35
	MB 2000SV	1100.0	2505	1110	1110	374.3	1474.3	2374.3	35
MBS vessels (horizontal)	MB 200SH	110.0	558	540	1026	39.2	149.2	239.2	22/28
	MB 250SH	137.5	558	540	1206	44.2	181.7	294.2	22/28


* The maximum pressure that can be applied to the cylinder under any installation conditions

** At typical working pressure

*** The maximum weight under fault conditions



Model Description	Dim. 'H'	Dim. 'W'	Dim. 'D'
MB 100SV	890 mm	410 mm	410 mm
MB 130SV	1100 mm	410 mm	410 mm
MB 200SV	1030 mm	535 mm	535 mm
MB 250SV	1210 mm	535 mm	535 mm
MB 300SV	1505 mm	535 mm	535 mm
MB 450SV	1545 mm	660 mm	660 mm
MB 750SV	1834 mm	756 mm	756 mm
MB 1000SV	2376 mm	806 mm	806 mm
MB 1500SV	2435 mm	960 mm	960 mm
MB 2000SV	2505 mm	1110 mm	1110 mm



Model Description	Dim. 'H'	Dim. 'W'	Dim. 'D'
MB 200SH	558 mm	540 mm	1026 mm
MB 250SH	558 mm	540 mm	1206 mm

Stuart Turner Limited reserves the right to amend specifications without notice.

Stuart Turner Ltd, Henley-on-Thames, Oxfordshire RG9 2AD Tel: +44 (0) 1491 572655
TechAssist Helpline +44 (0) 800 31 969 80
www.stuart-turner.co.uk

Issue 2025-01-01